



Wholesale Direct Inc.

5620 West 65th Street Chicago, IL 60638

Phone (773) 585-7200 Fax (773) 585-7279 Toll Free (888) 250-1700

www.wholealedirectinc.com



200 Bolt-On Eye

This eye features a 2-3/8" inside diameter (ID) loop and is one of our most popular eyes. It allows for an easy and secure connection on vertical oriented mounting structures.

Specifications:

Max GTW: 100,000 lbs.
Max Tongue Wgt: 15,000 lbs.
Inside Diameter: 2 3/8 in.



300 Bolt-On Eye

This eye has the same popularity and ease of install as our model 200 but features a larger inside diameter eye loop for those applications that need a larger eye loop.

Specifications:

Max Gross Trailer Weight: 100,000 lbs.
Max Tongue Weight: 15,000 lbs.
Inside Diameter: 3 in.

PREMIER MANUFACTURING CO.



240 Coupling

Designed as a direct retrofit to the mounting pattern of Premier's 135NT Swivel Coupling. The 240 has extra toughness and wear resistance that Premalloy users have come to expect.

Specifications:

Max Gross Trailer Weight: 45,000 lbs.
Max Tongue Weight: 6,000 lbs.
Ultimate Latch Capacity: 20,000 lbs.
Max Eye X-Section: 1 11/16 in.
Min Eye Opening: 2 1/16 in.



2200 Air Adjusted Coupling

Features the most popular mounting bolt pattern in the industry. Exceptional latch strength, easy operation and low maintenance. All 2000 series couplings can be operated with or without an air service chamber.

Specifications:

Max Gross Trailer Weight: 100,000 lbs.
Max Tongue Weight: 20,000 lbs.
Ultimate Latch Capacity: 60,000 lbs.
Max Eye X-Section: 1 13/16 in.
Min Eye Opening: 2 3/8 in.



600 Jiffy Jack

Our 600 Series Jiffy Jack out performs any other jack in its class. Unique "Jiffy Quick Release" for instant, one-lever lowering and retracting of the leg without cranking.

Specifications:

Capacity: 5,000 lbs. operational
10,000 lbs. static



700 Custom Jack

The Premier 700 Custom Jack has been engineered and built to the same stringent specifications as our 600. Designed for long life with minimal maintenance, the 700 is easily adapted to nearly any application.

Specifications:

Capacity: 5,000 lbs. operational
10,000 lbs. static