



# Wholesale Direct Inc.

5620 West 65th Street Chicago, IL 60638

Phone (773) 585-7200 Fax (773) 585-7279 Toll Free (888) 250-1700

www.wholesaledirectinc.com



## 238DB Drawbar Eye

This eye allows for a easy horizontal bolt on application.

### Specifications:

Max GTW: 90,000 lbs.  
Max Tongue Wgt: 8,000 lbs.  
Inside Diameter: 3 in.



## 135NT Swivel Coupling

Utility companies, construction, agriculture and military operations will all benefit from this swivel coupling. Swivel action eliminates torque between mated vehicles when traveling over rough, uneven terrain. (NOT to be used with a swivel-type drawbar eye.)

### Specifications:

Max Gross Trailer Weight: 30,000 lbs.  
Max Tongue Weight: 6,000 lbs.  
Ultimate Latch Capacity: 20,000 lbs.  
Max Eye X-Section: 1 11/16 in.  
Min Eye Opening: 2 1/16 in.

# PREMIER MANUFACTURING CO.



## 235NT Swivel Coupling

Premier's 235NT Swivel is a bit heavier duty than our 135NT Swivel for those extra tough jobs. When rough uneven ground is a problem, the 235NT Swivel may be the answer. (NOT to be used with a swivel-type drawbar eye.)

### Specifications:

Max Gross Trailer Weight: 60,000 lbs.  
Max Tongue Weight: 12,000 lbs.  
Ultimate Latch Capacity: 20,000 lbs.  
Max Eye X-Section: 1 11/16 in.  
Min Eye Opening: 2 1/8 in.



## 150 Combo Coupling

One of our most unique and versatile couplings. Whether you need to pull a trailer with an eye or ball connection, the 150 can do the job. Our patented side-swing latch helps prevent tailgate damage and keeps the profile compact.

### Specifications:

Max Gross Trailer Weight: 16,000 lbs.  
Max Tongue Weight: 2,000 lbs.  
Ultimate Latch Capacity: 5,000 lbs.  
Max Eye X-Section: 1 13/16 in.  
Min Eye Opening: 2 3/8 in.

### Ball Capacities:

150 w/2 in. Ball: MGTW: 10,000 lbs.  
150 w/2-5/16 in. Ball: MGTW: 10,000 lbs.  
150 w/1-7/8 in. Ball: MGTW: 2,500 lbs.



## 165 Receiver

Designed for superior strength, the 165 is a one-piece, solid steel casting, adjustable mount for 2 in. receiver-type connections. It allows for three different vertical height positions for mounting Premier's 150 & 160 couplings.

### Specifications:

Max Gross Trailer Weight: 10,000 lbs.  
Max Tongue Weight: 1,000 lbs.  
Pin Diameter: 5/8 in.



## 166 Receiver

The 166 Receiver is also a single, solid steel casting, adjustable mount receiver, except it is used in 2 1/2 in. receiver-type connections. It allows for three different vertical height positions for mounting Premier's 150 & 160 couplings.

### Specifications:

Max Gross Trailer Weight: 12,000 lbs.  
Max Tongue Weight: 1,200 lbs.  
Pin Diameter: 5/8 in.