



# WHOLESALE DIRECT INC.

Trailer Parts & Emergency Lighting Equipment

To order, call TOLL FREE: 888.250.1700  
or visit us online at [www.wholesaledirectinc.com](http://www.wholesaledirectinc.com)

## E-Flood® LiteBox®

- 45801 E-Flood LiteBox Standard System - Orange**
- 45821 E-Flood LiteBox Standard System - Yellow**
- 45805 E-Flood LiteBox Vehicle Mount System - Orange**
- 45825 E-Flood LiteBox Vehicle Mount - Yellow**
- 45807 E-Flood LiteBox Power Failure System- Orange**
- 45817 E-Flood LiteBox Power Failure System - Beige**
- 45806 E-Flood LiteBox (Without Charger) - Orange**
- 45816 E-Flood LiteBox (Without Charger) - Beige**
- 45826 E-Flood LiteBox (Without Charger) - Yellow**

- **Standard System:** Includes shoulder strap, AC and DC charge cords, and mounting rack
- **Vehicle Mount System:** Includes shoulder strap and vehicle-mountable hard-wire rack
- **Power Failure System:** Features "smart" power failure circuitry that automatically goes on when the power goes off. Includes AC and DC charge cords, and mounting rack



- Six C4® LEDs with wide pattern parabolic reflectors produce a smooth flood pattern
- 2 levels of lighting:
  - High: 4,000 candela; 615 lumens; runs 8 hours
  - Low: 2,150 candela; 330 lumens; runs 18 hours
- Sealed lead acid battery is rechargeable up to 500 times
- High impact ABS thermoplastic housing; rubberized impact bumper, lens ring and cushioned-grip handle ; IPX4 weather resistant
- 7.9 lbs.
- Rack meets requirements of NFPA 1901-14.1.11.2 (2003) mounted in any position

## Survivor® LED

Alkaline Model  
#90540



- C4® LED with 4 lighting modes:
  - High for a bright, far-reaching beam: 36,000 candela peak beam intensity; 140 lumens; runs 4 hours
  - Low for bright light and longer run times: 12,000 candela peak beam intensity; 47 lumens; runs 15 hours
  - Flash for signaling: runs 8 hours
  - Moonlight for low-level lighting and extended run times: runs 20 days
- Deep-dish parabolic reflector produces narrow beam; ideal for smoke-cutting applications; Optimum peripheral illumination
- Four "AA" alkaline battery pack provides fast replacement with readily available batteries; Also accepts rechargeable NiCd battery pack (purchased separately)
- A rubber dome push button switch is easy to use even when wearing heavy gloves
- High impact super tough nylon construction; unbreakable polycarbonate lens with silicone anti-scratch coating within a heavy-duty bezel
- IPX4 water-resistant; 2 meter impact resistance tested
- 7.06"; 13.1 oz
- UL Listed Class I, Div. 1, Groups C,D, T4; Class I, Div. 2, Groups A,B,C,D, T4; Class II, Div. 2, Groups F,G; Class III, T4

## Fire Vulcan® LED

Standard System  
#44450



- Features C4® LED with high and low beam, and two ultra-bright blue taillight LEDs that make certain you can be seen even in thick smoke
  - High: 80,000 candela; 145 lumens; runs 3 hours
  - Low: 40,000 candela; 70 lumens; runs 6 hours
- Deep-dish parabolic reflector produces a tight beam with optimum peripheral illumination
- Easy to operate toggle switch with 8 programmable switch functions
- Lightweight lithium ion battery recharges in 5 hours
- High impact ABS thermoplastic housing with rubberized cushioned-grip handle; reinforced D-rings; IPX7 waterproof to 1 meter for 30 minutes
- Includes a quick release buckle strap that works like a seatbelt buckle for fast and easy release/connection of shoulder straps
- Lightweight. Just 1.85 lbs.; floats
- Rack meets requirements of NFPA 1901-14.1.11.2 (2003) mounted in any position

## Knucklehead®

[Flood Model]

120V AC Fast Charge PiggyBack®

#90618



- Engineered optics feature dual C4 LEDs that produce a smooth flood pattern to illuminate your work area
- 4 modes:
  - High for a soft flood beam: 1150 candela peak beam intensity, 200 lumens, runs 3.5 hours
  - Low for when less light is needed and for longer run times: 350 candela peak beam intensity, 63 lumens, runs 16 hours
  - Moonlight for low-level lighting with extended run times: runs 20 days
  - Flash for signaling: 8 hour runtime
- Features a 210 degree articulating head that rotates a full 360 degrees
- Removable magnet with 135 lb pull strength features a replaceable rubber boot to protect painted surfaces
- Accepts rechargeable NiCd battery pack or 4 "AA" alkaline batteries
- PiggyBack charger simultaneously charges the light and a spare battery
- Rubber dome push-button switch is easy to operate even when wearing heavy gloves
- High-impact, super-tough nylon polymer construction for exceptional durability
- IPX4 water-resistant; 2 meter impact-resistance tested
- 9.2"; NiCd 23.1 oz.; Alkaline 18.3 oz.
- USTC Class I, Division 2, Groups A,B,C,D; Class II, Division 2, Groups F,G; Class III, Temp Code: T4
- Charger meets requirements of NFPA 1901-14.1.11.2 (2003) mounted in any position

## Stinger® LED HL™

12V DC

#75432



- Maximum illumination with a wide beam to search a large area
- Multi-function push-button switch lets you select three lighting modes and strobe:
  - High for a super-bright beam: 640 lumens; 22,000 candela peak beam intensity; runs 1.25 hours
  - Medium for bright light and longer run times: 340 lumens; 11,000 candela peak beam intensity; runs 2 hours
  - Low for light without glare and extended run times: 170 lumens; 5,500 candela peak beam intensity; runs 4 hours
- Strobe for disorienting or signaling your location; runs 3 hours
- NiMH battery is rechargeable up to 1000 times
- IPX4 water-resistant; 2 meter impact resistance tested
- Durable, anodized aluminum construction with removeable, rubberized anti-roll ring
- 8.41"; 12.4 oz

## Strion® LED HL™

120V AC/12V DC

#74751



- Maximum illumination with a wide beam to search a large area
- Multi-function push-button tail switch lets you select three lighting modes and strobe:
  - High for a super-bright beam: 500 lumens; 10,000 candela; runs 1 hour
  - Medium for bright light and longer run times: 250 lumens; 5,000 candela; runs 2 hours
  - Low for light without glare and extended run times: 125 lumens; 2,500 candela; runs 3.5 hours
  - Strobe for disorienting or signaling your location; runs 2.5 hours
- Lithium ion battery is rechargeable up to 1000 times; fully recharges in 3 hrs.
- IPX4 water-resistant; 2 meter impact resistance tested
- Durable, anodized aluminum construction; Borofloat high temperature glass lens
- Anti-roll head prevents the light from rolling away when you set it down
- 5.9"; 5.2 oz.

## SL-20XP® LED

120V AC/12V DC

#25103



- 8 watt halogen bulb delivers 16,000 candela peak beam intensity; 120 lumens
- 3 white LEDs provide 20 lumens
- Run time: 1.5 hours (halogen); 11.5 hours (LEDs); emergency backup LED (after full halogen run) = 1 hr. minimum
- Dual switches to select halogen light or LEDs; constant-on and momentary modes
- Tough nylon polymer body with non-slip rubber comfort grip; IPX4 water-resistant; 1 meter impact resistance tested
- NiCd battery rechargeable up to 1,000 times
- Power Failure Feature- when light is in charger in the "on" position, it will illuminate automatically when power is lost
- 13.2"; 17.6 oz.